



PRODUCT TECHNICAL SPECIFICATION  
**MASTER VITRO – MVV1500RB**

FCP\_040\_01\_EN



**DESCRIPTION:**

Tank for domestic hot water (DHW) **STORAGE**.

For vertical installation on floor. Manufactured in **VITREOUS ENAMELLED STEEL** according to the DIN4753 standard, with mould-injected rigid **PU thermal insulation**. As option, external PVC lining, to be supplied separately. Permanent cathodic protection "**Lapesa Correx-Up**".

Equipped with DN400 side manhole for inspection / cleaning tasks, or optionally, for the installation of a stainless steel plate to allocate electric heating elements.

**MAIN CHARACTERISTICS**

Total capacity:	Total	1500	L
Maximum working pressure:		8	bar
Maximum working temperature:		90	°C
Connections:	ww: DHW outlet	2	" M
	kw: cold water inlet	2	" M
	z: recirculation	1 ½	" M
	e: drain	1 ½	" M
	R: side connection for electric element	2	" M
	pc: "lapesa correx-up" connection	1 ½	" M
	tm: sensor connection	¾	" M
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	154	W
External dimensions:	D: Diameter	1360	mm
	H: Height (without connections)	1830	mm
	Diagonal (without connections)	2280	mm
Packaging dimensions:	Width / Height	1360 x 1900	mm
Weight:	Without packaging / With packaging	400 / 400.5	kg